



ecom-B

- Sensor Options: O₂, CO, NO
- Calculated NO_x, CO₂, Efficiency Excess Air
- CO Bypass Function
- IR Printer Option
- 7ft Sample Line, 9in Probe
- Pump Strength up to 1lpm
- Aluminum Housing



ecom-B Plus

- Sensor Options: O₂, CO, NO
- Electronically Monitored Condensate Trap
- CO Bypass Function
- Integrated Printer
- 7ft or 9ft Sample Line, 9in or 12in Probe
- Enhanced Filtration
- Aluminum Housing



ecom-CL 2

- Sensor Options: O₂, CO, NO
- Electronically Monitored Condensate Trap
- CO Bypass Function
- Integrated Printer
- 7ft Sample Line, 9in Probe
- Enhanced Filtration
- All-in One Unit – Aluminum Case and Analyzer



ecom-D

- Sensor Options: O₂, CO, NO, NO₂, SO₂, C_xH_y, H₂S, CO₂ & CH₄ IR
- Electronically Monitored Condensate Trap
- Peltier Cooler Option
- IR Printer Option
- WIFI and free App
- 9ft or 15ft Sample Line, 12in Probe
- Aluminum Housing
- Pump Strength up to 1lpm



ecom-EN3-Series (compliance level analyzer)

- Sensor Options: O₂, CO, NO, NO₂, SO₂, C_xH_y, H₂S, CO₂ & CH₄ IR
- Automated Moisture Removal
- Peltier Cooler
- Advanced Filtration
- Onboard Printer
- WIFI and free App, Optional Compliance SW
- Bluetooth Option
- Pump Strength up to 2.6lpm
- 15ft Sample Line, 12in Probe



ecom-J2KN Series (compliance level analyzer)

- Sensor Options: O₂, CO, NO, NO₂, SO₂, C_xH_y, H₂S, CO₂ & CH₄ IR
- Automated Moisture Removal
- Industrial Cooling & Filtration
- Handheld Control Unit
- Onboard Printer
- WIFI or Bluetooth Option
- Optional Fresh Air Purge Valve
- Pump Strength up to 2.6lpm
- 15ft Sample Line, 12in Probe



ecom-J2KNpro TECH (compliance level analyzer)

- Can be equipped with NDIR, PAS, Chemiluminescence & EC Sensors
- Automated Moisture Removal
- Industrial Cooling & Filtration
- Handheld Control Unit
- Onboard Printer
- WIFI or Bluetooth Option
- Fresh Air Purge Valve
- Pump Strength up to 2.6lpm
- 15ft Sample Line, 12in Probe



ecom-Software Options

- For D6522 & SQMD Compliance Testing
- Generation of Snapshot Report
- MS Operating System Based
- Free App for Single Snapshot and Remote Display (iOS and Android)
- Transferable Customer & Equipment Database
- SD Card Upload Function



ecom-Manometers (differential pressure meters)

- ecom-UNO:
Range +/- 32 iwc
Resolution .004 iwc
Over Range +/- 120 iwc
- ecom-DP (single or dual channel):
Range Opt. +/- 0 to 602 iwc Resolution .004 iwc
Range Opt +/- 0 to 28 iwc Resolution .0004 iwc
- ecom-DP (Engine - dual)
Range 0 to 145 PSI / 0 to 14.5 PSI Resolution .01 PSI



ecom-LS Series (leak detection)

- ecom-LSG - Gas Leak Detector
Optical and Acoustical Warning
Flex Arm